


NOTES:

1. WIRE FENCE SHALL BE FASTENED TO T-POSTS WITH METAL WIRE TIES OR PLASTIC ZIP TIES.
2. TREE PROTECTION FENCE SHALL BE INSTALLED ACCORDING TO THE APPROVED PLANS AND ACCORDING TO DIRECTION BY THE URBAN FORESTER. FENCE SHALL BE A MINIMUM OF SIX (6') FOOT HIGH CHAIN LINK FENCE ATTACHED TO STEEL POSTS. WHERE FENCING IS INSTALLED WITHIN THE ROOT ZONES OF EXISTING TREES, POSTS SHALL BE DRIVEN INTO THE GROUND A MINIMUM OF TWO (2) FEET AND SHALL NOT BE SET IN CONCRETE. OTHERWISE FENCING SHALL MEET ALL REQUIREMENTS OF VESCH SAFETY FENCE STD. & SPEC 3.01.
3. SILT FENCING, WHEN SPECIFIED FOR THE SAME LOCATION, MAY BE ATTACHED DIRECTLY TO TREE PROTECTION FENCING.
4. ALL L.O.D./TREE PROTECTION FENCING MUST BEAR HEAVY-DUTY, WEATHERPROOF SIGNS INDICATING THAT FENCE LINE MARKS EDGE OF TREE PROTECTION AREA. SIGNS ARE TO BE IN BOTH SPANISH AND ENGLISH AND MOUNTED ON THE INSIDE OF THE L.O.D. NO LESS THAN EVERY 30' ON CENTER. REFER TO 6' CHAIN LINK TREE PROTECTION FENCE DETAIL (311300.1) FOR SIGN DESCRIPTION AND REQUIREMENTS.
5. TEMPORARY L.O.W./TREE PROTECTION FENCE SHALL BE A MINIMUM OF FIVE (5') FOOT HIGH FOURTEEN (14) GAGE WELDED WIRE MESH ATTACHED TO STEEL T-POSTS DRIVEN AT LEAST EIGHTEEN (18) INCHES DEEP AND SPACED NO MORE THAN SIX (6) FEET APART, POSTS TO EXTEND ABOVE GROUND AT LEAST THE HEIGHT OF THE FENCE.



TREE PROTECTION FENCE - WIRE

ELEVATION
311300.21 (2026)

NOT TO SCALE